

Dotek

Dotek R1 Series

MPEG-2 SD-SDI Encoder



Features

- (1) Support MPEG-2 MP@ML(4:2:0) encoding
- (2) Support SD-SDI, HDMI, CVBS signal input
- (3) Support full hardware ASI and IP output(TS over IP)
- (4) Support 576i, 480i video format input
- (5) Output bit rate can be adjust continuously, easy to operate
- (6) Support a variety of interface input and output
- (7) SDT insert
- (8) Support LCD display, front panel button operation and remote Web network management control
- (9) Automatic recognition signal is supported without manual selection
- (10) High reliability design, stable operation
- (11) Double switch power supply design, wide voltage range, power supply system for a long time reliable work

Introduction

Dotek R1 series MPEG-2 SD encoder is a kind of easy to operate and powerful encoder. Support SDI, CVBS, HDMI signal interface input, real-time coding of audio and video through the encoder to form a multiplexed code stream(MPTS), the output interface is IP and ASI, fully comply with MPEG-2

standard, has strong compatibility, mainly used in cable TV front end and IPTV live broadcast system SD signal relay.

Technical Specifications

Input interface	
HD/SD-SDI	BNC 75 Ω
HDMI	HDMI 1.3
CVBS	BNC 75 Ω
Resolution	576i50, 480i60
Output interface	
ASI	BNC 75 Ω DVB-ASI standard
IP	RJ45(1000M), IP/UDP
Video encoding	
Video encoding format	MPEG-2
Bit rate	2Mbps-20Mbps
Rate control	CBR, VBR
GOP structure	IBBP
Audio encoding	
Sample rate	32KHz, 44.1KHz, 48KHz
Bit rate	64K, 128K, 192K, 256K, 384Kbps
Audio encoding format	MPEG-1 layer 1/2, AAC
Channel	Mono, stereo
Control	
Management	Web-based remote network management software
Management interface	RJ45(100M)
LCD display	1
Operation buttons	6
Physical	
Dimension(H \times W \times D, mm)	44 \times 433 \times 343(mm)
Operation temperature	0-50 $^{\circ}$ C
Relative humidity	0-95%, non-condensing
Power supply	130-260VAC, 50/60Hz

Doteck

Doteck Digital Technologies

Suite 819, Building C, Suite 11A, 11B, 11D, Tower 2, International Innovation Park, No. 2, Shangdi Info Road, Haidian District, BEIJING, CHINA, Postcode: 100085

Tel: +86-10-62120151

Mobile: +86-13910290608

Contact: LI XINJIAN

E-mail: Doteck@126.com

Welcome to visit our website for more info: www.Doteck.com