

# Doteck

## Doteck R8 Series

### 8K UHD H.265 Encoder



#### Features

- (1) Industrial grade 19 inch 1U standard equipment with built-in dual power supply
- (2) Web-based remote network management software
- (3) Support H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3 (optional) encoding
- (4) Support MPEG-1 layer 2, MPEG-1 layer 3, LC-AAC, HE-AAC, AC3, EAC3 ,DRA audio encoding format

- (5) Support three video acquisition methods: 4-channel 12G-SDI, or 4-channel 6G-SDI, or 4-channel 3G/HD/SD-SDI
- (6) Support 4320p, 2160p, 1080p, 1080i, 720p, 576i, 480i video input
- (7) Support SPTS, MPTS over UDP, FLV over RTMP, HLS over HTTP transmission stream IP input
- (8) Support UDP, RTP, RTSP, RTMP, HTTP, SRT network protocol output
- (9) Support the output video stream delay settings, delay time 0-120 seconds custom
- (10) Support internal multiplexer, which can multiplex SPTS program stream after multiplexing and transcoding into MPTS program stream
- (11) Support two gigabit ethernet ports, can be flexible configuration of IP program input and output physical channels
- (12) Support 10bit HDR
- (13) Support picture, caption overlay, multi-screen splicing and other software functions customization
- (14) Support main and standby signal switching function
- (15) Support GOP length, GOP structure and bit rate control buffer settings
- (16) Support CBR, VBR rate control mode
- (17) Stable operation of the equipment, supporting 7x24 hours uninterrupted work

## **Introduction**

Dotek R8 series 8K UHD H.265 encoder adopts standard 1U chassis structure, is a high quality broadcast audio and video real-time encoder product. This product not only has the traditional H.264/AVC video encoding ability, but also supports international video standard H.265/HEVC and China's independent intellectual property rights video standard AVS+, AVS, AVS2, AVS3 (optional) encoding format.

Dotek R8 series 8K UHD H.265 encoder can compress 4-channel 12G-SDI, or 4-channel 6G-SDI, or 4-channel 3G/HD/SD-SDI digital videos into any of the above video encoding formats in real-time through the encoding module, and can also convert 1-channel 8K IP input stream, or 4-channel 4K IP input

stream, or 16-channel HD IP input stream or 32-channel SD IP input stream into any of the above video encoding formats in real-time.

### Technical Specifications

<b>SDI input</b>	
SDI signal format	12G/6G/3G/HD/SD-SDI
Channel	4-channel 12G-SDI, or 4-channel 6G-SDI, or 4-channel 3G/HD/SD-SDI
Resolution	4320p60/50 2160p60/50/30/25 1080p60/50/30/25 1080i60/50 720p60/50/30 576p25, 480p30 576i50, 480i60
Interface	BNC 75Ω
<b>Video encoding</b>	
Video encoding format	H.265/HEVC, H.264/AVC, AVS+, AVS, AVS2, AVS3 (optional)
Bit rate	1.0Mbps~280.0Mbps
Rate control	CBR, VBR
Video pretreatment	De-interleaving
<b>Audio encoding</b>	
Audio encoding format	MPEG-1 layer 2, MPEG-1 layer 3, LC-AAC, HE-AAC, AC3, EAC3, DRA
Sampling rate	48KHz, 44.1KHz, 32KHz
Channel	Mono, stereo, 5.1, 7.1 surrounding stereo sound
Bit rate	64Kbps~1024Kbps
<b>IP stream input</b>	
Input interface	RJ45
Rate	1000Mbps
Stream encoding format	H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3 (optional)
Network protocol	UDP, RTP, RTSP, RTMP, HTTP, SRT
Transport stream format	SPTS, MPTS, FLV, HLS
<b>IP stream output</b>	
Output interface	RJ45
Rate	1000Mbps
Stream encoding format	H.265/HEVC, H.264/AVC, AVS, AVS+, AVS2, AVS3 (optional)
Network protocol	UDP, RTP, RTSP, RTMP, HTTP, SRT
Transport stream format	SPTS, MPTS, FLV, HLS
<b>Control</b>	

Management	Web-based remote network management software
<b>Physical</b>	
Dimension(H×W×D, mm)	44×433×636(mm)
Operation temperature	0-50℃
Relative humidity	0-95%, non-condensing
Power supply	130-260VAC, 50/60Hz

# Doteck

## **Doteck Digital Technologies**

Suite 819, Building C, Suite 11A, 11B, 11D, Tower 2, International Innovation Park, No. 2, Shangdi Info Road, Haidian District, BEIJING, CHINA, Postcode: 100085

Tel: +86-10-62120151

Mobile: +86-13910290608

Contact: LI XINJIAN

E-mail: [Doteck@126.com](mailto:Doteck@126.com)

Welcome to visit our website for more info: [www.Doteck.com](http://www.Doteck.com)